

INDUSTRIAL VACUUM SYSTEMS

VacTruck



VacTruck

Powerful vacuum loader for bulk material. Vacuum cleaning and vacuum conveying in cement plants, steel plants, power plants and similar sectors of industry.









wieland lufttechnik Wetterkreuz 12 91058 Erlangen Germany Phone +49 9131 60 67-0 Fax +49 9131 60 44 01 info@wieland-luft.com www.wieland-luft.com

VacTruck is available in three power versions und with three different collection containers.


VacTruck - basic model



VacTruck - BigBag



VacTruck - Jumbo



Unit	3700-50	6000-50	6000-80
m³/h	3700	6000	6000
mbar	550	550	900
mbar	500	500	800
DN	150		
m ³	9		
m³	9		
m ³	15		
m ²	18	24	24
m²	20		
dB(A)	82		
	m ³ /h mbar DN m ³ m ³ m ³ m ² m ²	m³/h 3700 mbar 550 mbar 500 DN	$\begin{array}{c ccccc} m^3/h & 3700 & 6000 \\ mbar & 550 & 550 \\ mbar & 500 & 500 \\ DN & & 150 \\ \hline m^3 & & 9 \\ m^3 & & 9 \\ m^3 & & 15 \\ m^2 & 18 & 24 \\ m^2 & & 20 \\ \hline \end{array}$

VacTruck - one system, three models

Available as VacTruck 3700-50, 6000-50 and 6000-80. Distinguishes itself by its compact and straight-forward design. VacTruck is designed for three-axle trucks. The extracted suction material is discharged to the rear through its large discharge opening. Robust and safe technology ensure a very high level of availability.

If the suction material needs to be discharged in a dust free way, VacTruck can be equipped with a discharge system for 1000 litre BigBags. The BigBags are filled in a controlled way by means of a discharge slide gate in the discharge door. The required discharge height for this is achieved by a higher mounting position of the collection container. This offers additional storage space below the collection container for suction hoses and accessories. A guard rail makes sure that the load can be securely tied down.

A longer wheel base of the truck allows for a larger collection capacity of 15,000 litres. This model is particularly suitable for light weight suction material. The unit disposes of a tipping discharge system to the rear.

VacTruck - distinctive characteristics

- Compact filter elements with AirShock[®] filter cleaning device - safe and fast replacement of the main filter.
- Completely electrically grounded as standard equipment. Sources of ignition must not be extracted
- The vacuum pump is driven by the truck engine no separate Diesel engine required.
- Optional equipment to extract liquid materials.
- Optional equipment to transport liquid materials.

* max. vacuum pump, ** reflexion free

0516-377/1