

## CLENA KS 2 PUMP INSTALLATION

### Product Information

- Powerful and simple build high pressure cleaner
- Built in a stationary frame
- HAWK pumps with ceramic pistons
- Easy to operate and maintain
- Long lifetime – low costs
- Build with or without stainless steel cover plate
- Controls on request, PLC etc.
- Optional mounting of water tank
- Shared or individual water inlet.



### Technical Specifications

MODEL	PRESSURE	WATER VOLUME	ENGINE	MAX TEMP. INLET.	PRODUCT NUMBER
KS 200 - 40	200 bar	40 l/min	32 amp, 2 x 7,5 kW	65 °C	30.203.040
KS 160 – 50	160 bar	50 l/min	32 amp, 2 x 7,5 kW	65 °C	30.164.050
KS 160 – 60	160 bar	60 l/min	50 amp, 2 x 11 kW	65 °C	30.163.060
KS 200 – 60	200 bar	60 l/min	50 amp, 2 x 11 kW	65 °C	30.203.060
KS 150 - 80	150 bar	80 l/min	50 amp, 2 x 11 kW	65 °C	30.203.080

### Additional Information

Delivered without additional equipment unless otherwise agreed.

**Note:**

- Can be built in 3x400/440/230v

*Do not hesitate to contact us if you have any special requirements for a machine as we can build them according to your needs.*