

CLENA MODEL KS-KH

Product Information

- Simple and practical build high pressure cleaner
- Built in stationary frame with stainless steel cover plate (Suspension included)
- HAWK pumps with ceramic pistons
- Automatic start/stop
- Easy to operate and maintain
- Long lifetime – low costs



Technical Specifications

| MODEL | PRESSURE | WATER VOLUME | ENGINE | MAX TEMP. INLET. | PRODUCT NUMBER |
|-------------|----------|--------------|----------------|------------------|----------------|
| KS 160 – 15 | 160 bar | 15 l/min | 10 amp, 4 kW | 65 °C | 30.163.015 |
| KS 160 – 20 | 160 bar | 20 l/min | 13 amp, 5,5 kW | 65 °C | 30.163.020 |
| KS 200 – 15 | 200 bar | 15 l/min | 13 amp, 5,5 kW | 65 °C | 30.203.015 |
| KS 200 – 20 | 200 bar | 20 l/min | 16 amp, 7,5 kW | 65 °C | 30.203.020 |
| KS 160 – 25 | 160 bar | 25 l/min | 16 amp, 7,5 kW | 65 °C | 30.163.025 |
| KS 200 – 30 | 200 bar | 30 l/min | 25 amp, 11 kW | 65 °C | 30.203.030 |
| KS 170 – 34 | 170 bar | 34 l/min | 25 amp, 11 kW | 65 °C | 30.173.034 |
| KS 150 – 40 | 150 bar | 40 l/min | 25 amp, 11 kW | 65 °C | 30.153.040 |
| KH 160 – 15 | 160 bar | 15 l/min | 10 amp, 5,5 kW | 85 °C | 30.260.015 |
| KH 160 – 18 | 160 bar | 18 l/min | 13 amp, 5,5 kW | 85 °C | 30.260.018 |
| KH 160 – 27 | 160 bar | 27 l/min | 20 amp, 9,2 kW | 85 °C | 30.260.027 |

Additional Information

Included equipment:

- 10 m. high pressure hose
- Pistol and double lance
- 10 m. power cable

Note:

- Can be built in 3x400/440/230v

Do not hesitate to contact us if you have any special requirements for a machine as we can build them according to your needs.